SERIES 1000 MEDIUM DUTY CANTILEVER RACK

EXCELLENT LOW COST STORAGE SYSTEM • IDEAL FOR MAINTENANCE DEPARTMENTS AND TOOL ROOMS

MECO OMAHA SERIES 1000 UPRIGHTS, ARMS and **BRACE SETS** are not interchangeable with any other rack series.

High quality MECO OMAHA Series 1000 Cantilever Rack is designed for use 9 where heavier capacities are not required. This rack is similar to our popular heavier duty racks except for the use of lighter gauge steel and smaller dimensions of component parts. Available in 6', 7', 8', 10' and 12' single and double sided uprights with a choice of eight standard brace lengths (measured on center) to accommodate 12", 18", 24", 30", 36", 42" and 48" straight or inclined arms. Arms are completely adjustable on 3" centers up and down the full length of the uprights. Two or more uprights can be assembled into a continuous system.

This sturdy and stable rack is as convenient and versatile as the heavier duty racks but priced lower to reflect the reduced capacity. Installation is quick and easy. Racks can be tailored to your individual requirements. Uprights facilitate manual loading and unloading. Open base design affords easy forklift accessibility. Ideal for storing bar stock, pipe, tubing, lumber and many lightweight or hard-to-stock items that must be kept off the floor.



FVFRY ITEM READILY AVAILABLE

		V/ (IL/ (DLL
 AI 	I WEIGHTS INCLUDE	HARDWARE

SINGLE SIDED UPRIGHTS						
HEIGHT OF	LENGTH	LENGTH	WEIGHT	CAPACITY	MODEL	
UPRIGHT	OF BASE	OF ARM	(LBS)	(LBS)	NO.	
6'	33"	12" & 18"	82	8,100 & 6,600	MU633	
	33"	24"	82	5,500	MU633	
	45"	30"	90	4,700	MU645	
	45"	36"	90	4,100	MU645	
	57"	42" & 48"	100	3,700 & 3,300	MU657	
7'	33"	12" & 18"	89	7,900 & 6,400	MU733	
	33"	24"	89	5,300	MU733	
	45"	30"	97	4,600	MU745	
	45"	36"	97	4,100	MU745	
	57"	42" & 48"	107	3,700 & 3,300	MU757	
8'	33"	12" & 18"	96	7,600 & 6,300	MU833	
	33"	24"	96	5,300	MU833	
	45"	30"	104	4,500	MU845	
	45"	36"	104	4,000	MU845	
	57"	42" & 48"	114	3,600 & 3,200	MU857	
10'	33"	12" & 18"	110	7,100 & 5,900	MU1033	
	33"	24"	110	5,000	MU1033	
	45"	30"	118	4,400	MU1045	
	45"	36"	118	3,800	MU1045	
	57"	42" & 48"	128	3,400 & 3,100	MU1057	
12'	33"	12" & 18"	124	6,500 & 5,400	MU1233	
	33"	24"	124	4,700	MU1233	
	45"	30"	132	4,100	MU1245	
	45"	36"	132	3,700	MU1245	
	57"	42" & 48"	142	3,300 & 3,000	MU1257	
	, , , , , , , , , , , , , , , , , , , ,					

STRAIGHT ARMS						
LENGTH	CAPACITY	WEIGHT	MODEL NO. WITHOUT LIP	MODEL NO. WITH LIP		
12" 18" 24" 30" 36" 42" 48"	1000 lbs 750 lbs 600 lbs 500 lbs 400 lbs 350 lbs 300 lbs	6 lbs 7 lbs 8 lbs 9 lbs 10 lbs 13 lbs 15 lbs	MSA12 MSA18 MSA24 MSA30 MSA36 MSA42 MSA48	MSA12L MSA18L MSA24L MSA30L MSA46L MSA42L MSA48L		

STRAIGHT ARMS have a minimum pitch of 3/8" per foot to compensate for	
deflection. Arm capacities are based on an evenly distributed load.	

DOUBLE SIDED UPRIGHTS						
HEIGHT OF	LENGTH	LENGTH	WEIGHT	CAPACITY	MODEL	
UPRIGHT	OF BASE	OF ARM	(LBS)	(LBS)	NO.	
6'	54"	12" & 18"	99	16,200 & 13,200	MDU654	
	54"	24"	99	11,000	MDU654	
	78"	30"	115	9,400	MDU678	
	78"	36"	115	8,200	MDU678	
	102"	42" & 48"	135	7,400 & 6,600	MDU6102	
7'	54"	12" & 18"	106	15,800 & 12,800	MDU754	
	54"	24"	106	10,600	MDU754	
	78"	30"	122	9,200	MDU778	
	78"	36"	122	8,200	MDU778	
	102"	42" & 48"	142	7,400 & 6,600	MDU7102	
8'	54"	12" & 18"	113	15,200 & 12,600	MDU854	
	54"	24"	113	10,600	MDU854	
	78"	30"	129	9,000	MDU878	
	78"	36"	129	8,000	MDU878	
	102"	42" & 48"	149	7,200 & 6,400	MDU8102	
10'	54"	12" & 18"	127	14,200 & 11,800	MDU1054	
	54"	24"	127	10,000	MDU1054	
	78"	30"	143	8,800	MDU1078	
	78"	36"	143	7,600	MDU1078	
	102"	42" & 48"	163	6,800 & 6,200	MDU10102	
12'	54"	12" & 18"	141	13,000 & 10,800	MDU1254	
	54"	24"	141	9,400	MDU1254	
	78"	30"	157	8,200	MDU1278	
	78"	36"	157	7,400	MDU1278	
	102"	42" & 48"	177	6,600 & 6,000	MDU12102	

INCLINED ARMS					
LENGTH CAPACITY		WEIGHT	MODEL NO. WITHOUT LIP	MODEL NO. WITH LIP	
12"	1000 lbs	6 lbs	MIA12	MIA12L	
18"	750 lbs	7 lbs	MIA18	MIA18L	
24"	600 lbs	8 lbs	MIA24	MIA24L	
30"	500 lbs	9 lbs	MIA30	MIA30L	
36"	400 lbs	10 lbs	MIA36	MIA36L	
42"	350 lbs	13 lbs	MIA42	MIA42L	
48"	300 lbs	15 lbs	MIA48	MIA48L	

INCLINED ARMS have a pitch of 20 degrees or approximately 4.36" per foot. Arm capacities are based on an evenly distributed load.

Note that arm lips are not intended to bear any portion of the load.

There and an inpo are not interned to bear any person of the load.						
	BRACES FOR 6' - 10' U	PRIGHTS - SET OF TWO	BRACES FOR 12' UPRIGHTS - SET OF THREE			
LENGTH*	MODEL NO. WEIGHT		MODEL NO.	WEIGHT		
23"	M2B24	21 lbs	M3B24	31 lbs		
35"	M2B36	28 lbs	M3B36	41 lbs		
41"	M2B42	31 lbs	M3B42	47 lbs		
47"	M2B48	35 lbs	M3B48	52 lbs		
59"	M2B60	42 lbs	M3B60	62 lbs		
71"	M2B72	49 lbs	M3B72	73 lbs		
83"	M2B84	56 lbs	M3B84	83 lbs		
95"	M2B96	63 lbs	M3B96	94 lbs		

^{*} Length of braces is measured from center of upright to center of upright.

20 BUYER'S GUIDE CANTILEVER RACK